



API X GR & MTRS

800-764-7473 • BisonPipe.com

OD	DESCRIPTION	FOOTAGE
36	36 X 1.500 DSAW API 5L X56, BARE, IMP, BOX X PIN, MTRS	630
	36 X .465 ERW API 5L X70 483 CAT 2 GR, FBE, IMP, BXB, MTRS	3,289
	36 X .465 SPIRALWELD API 5L X70, FBE, DOM, MIXED ENDS, MTRS	26,455
30	30 X .625 DSAW API 5L X65, BARE, BXB, DURABOND, M&M DOM, MTRS	573
	30 X .618 DSAW API 5L X70, ARO, M&M DOM, MTRS	762
	30 X .429 SPIRALWELD API 5L X70, FBE, DOM MAN ONLY, BXB, MTRS	2,759
28	28 X .752 DSAW API 5L X52 X56, BARE, IMP, BOXxPIN, MTRS	868
	28 X .750 DSAW API 5L X56, BARE, IMP, MTRS	1,885
24	24 X .500 ERW API 5L X70, ARO, IMP, BXB, MTRS	1,340
	24 X .375 API 5L X65 GR, FBE, BXB, M&M DOM, MTRS	2,273
22	22 X .375 DSAW API 5L X46, SPIRALWELD, BARE, IMP, MTRS	4,310
18	18 X .375 ERW API 5L X42 A53 B, BLK LAQ, IMP, BXB, MTRS	6,977
16	16 X .500 ERW API 5L X60, ARO/FBE, DOM, BXB, MTRS	864
	16 X .500 ERW API 5L X52 A53 GR B, ARO/FBE, IMP, BXB/BXTC, MTRS	506
	16 X .375 ERW API 5L X52, CTD, IMP, BXB, MTRS	534
	16 X .281 ERW X52, SURPLUS, FBE, MIXED ENDS, 0-1 MW	2,600
14	14 X .500 ERW API 5L X52, POWERCRETE, DOM, BXB, MTRS	780
	14 X .500 ERW API 5L X52, FBE, DOM, BXB, MTRS	1,274
	14 X .500 ERW API 5L X52, BARE, DOM, BXB, MTRS	2,369
	14 X .600 SEAMLESS API 5L X65, FBE, M&M DOM, MTRS	1,450
	14 X .600 SEAMLESS API 5L X65, BARE, M&M DOM, MTRS	1,398



API X GR & MTRS

800-764-7473 • BisonPipe.com

OD	DESCRIPTION	FOOTAGE
12	12 3/4 X .469 SEAMLESS API 5L GR B X65, ARO/FBE, IMP, BXB, MTRS	12,275
	12 3/4 X .469 SEAMLESS API 5L GR B X65, BARE, IMP, BXB, MTRS	3,039
	12 3/4 X .375 ERW API 5L X52, ARO, M&M DOM, BXB, MTRS	3,336
	12 3/4 X .281 ERW API 5L X52, FBE, M&M DOM, BXB, MTRS	1,058
10	10 3/4 X .500 ERW API 5L X65, ARO/FBE, DOM, MTRS	2,735
8	8 5/8 X .438 SEAMLESS API 5L X60, BARE, IMP, BXB, MTRS	750
3	3 1/2 X .600 SEAMLESS API 5L A53 GR B X42, SURPLUS, FBE, DOM, BXB, MTRS	907
	3 1/2 X .300 ERW API 5L X52, BARE, DOM, MTRS	1,069
2	2 3/8 X .154 ERW API 5L X52, BARE, MTRS	680

Want to see more sizes & specs?

Call Today!

800-764-7473